# FR-7M3024 • FR-7M3024P • FR-7M3024BT

L2+ Managed 24-port 24x10/100/1000BASE-T (Non-PoE/PoE+/PoE++)RJ45 Auto-MDI/MDI-X with Redundant DC Power Inputs









## Main Features

### Layer 2+ Features

- ERPSv2 redundant ring (<20ms) & STP/RSTP/MSTP
- 802.1Q VLAN, QinQ, and GVRP
- Dynamic LACP and static trunking
- IGMP Snooping v1/v2/v3 and Fast Leave
- QoS rate limiting, CoS, and 802.1p priority
- IPv4 static routing & VLAN interfaces

### Software Management

- WebGUI, CLI, and NMS management
- SNMPv1/v2c/v3, LLDP, and SNTP
- Port mirroring and HTTP firmware updates
- Modbus TCP/RTU & serial protocol conversion

### Security

- IEEE 802.1X and RADIUS authentication
- MAC/IP-based ACL
- DHCP Snooping with Option 82
- SSHv2 and TLSv1.2 secure access

### PoE Functions

- 802.3at/bt PoE (30W/90W per port)
- PoE scheduling / Auto PD reboot
- Long reach PoE 250m, data rate at 10Mbps
- PoE budget & usage threshold monitoring

### Industrial Features

- Operating temperature -40°C to +75°C
- Redundant DC power inputs / Alarm relay
- High ESD/surge protection / Fanless
- DIP switch (RSTP / VLAN / SFP speed)
- NDAA & RoHS compliant

CE FC

Protected by hardware warranty
Advance replacement. Global coverage.

View policy on Fiberroad's website.

# Product Specifications

## FR-7M3024 • FR-7M3024P • FR-7M3024BT



| Product | FR-7M3024 | FR-7M3024P | FR-7M3024BT |
|---|---|---|---|
| **Interface** | | | |
| RJ45 Ports | 24x10/100/1000BASE-T | | |
| Console | 1x RJ45-to-RS232 Serial Port(115200) | | |
| DIP Switch | RSTP; VLAN; SFP speed | | |
| **Electrical and Mechanical** | | | |
| Input Voltage | Dual 9-56VDC | Dual 48-56VDC | Dual 52-56VDC |
| Power Consumption | 10 Watts Max (without PoE load) | | |
| PoE Ports | \ | Port 1 to 8 IEEE802.3 af/at | Port 1 to 8 IEEE802.3 af/at/bt |
| PoE Power Supply Type | End-span | | |
| Power Supply Pin | \ | 1/2(+),3/6(-) | 1/2(+), 3/6(-) or 4/5(+), 7/8(-) |
| Max Power Per Port | \ | 30W | 90W |
| Max. PoE Power Budget | \ | 240W | 240W<br>(54V Single-Sourced Dual Inputs ) |
| Surge Protection | ±6kV DC, ±4kV RJ45 | ±6kV DC, ±6kV RJ45 | |
| Enclosure | IP40 Aluminum Case | | |
| Dimension | 160 x 132 x 70mm, 1.45kg | | |
| **Standards** | | | |
| IEEE 802.3 | 10BaseT | | |
| IEEE 802.3u | 100BaseT(X) and 100BaseFX | | |
| IEEE 802.3ab | 1000BaseT(X) | | |
| IEEE 802.3x | Flow Control | | |
| IEEE 802.1p | Class of Service | | |
| IEEE 802.1Q | VLAN Tagging | | |
| IEEE 802.1x | Authentication | | |
| IEEE 802.3ad | Port Trunk with LACP | | |
| IEEE 802.1D | Spanning Tree Protocol | | |

# Product Specifications

## FR-7M3024 • FR-7M3024P • FR-7M3024BT



| Product | FR-7M3024 | FR-7M3024P | FR-7M3024BT |
|---|---|---|---|
| **Standards** | | | |
| IEEE 802.1w | Rapid Spanning Tree Protocol | | |
| IEEE 802.1s | Multiple Spanning Tree Protocol | | |
| IEEE 802.1ad | Q-in-Q tunneling | | |
| **Switching** | | | |
| Switch Architecture | Store-and-Forward | | |
| Switch Fabric | 56Gbps/non-blocking | | |
| Forwarding Rate | 35.71Mpps(64-byte packet size) | | |
| Packet Buffer Size | 4 Mbits | | |
| Maximum Packet Length | 10K bytes | | |
| MAC Address Table | 8K entries, automatic source address learning and aging | | |
| Flow Control | IEEE 802.3x pause frame for full duplex, Back pressure for half duplex | | |
| **Software Features** | | | |
| Port Configuration | Port(Admin Status) disable/enable<br>Copper Port: Auto-negotiation 10/100/1000Mbps full and half duplex mode selection<br>Fiber Port: 100M/1000M speed selection<br>Flow Control disable/enable<br>Power saving(EEE) disable/enable<br>Each port description | | |
| Port Status | Display each ports' speed duplex mode, link status, flow control status,<br>auto negotiation status, Fiber Port Information, Port Traffic | | |
| Port Mirroring | Source Ingress/ Egress Port/ Both, Many-to-1 monitor | | |
| VLAN | Up to 4K VLAN groups, out of 4094 VLAN IDs<br>IEEE 802.1Q tag-based VLAN<br>IEEE 802.1AD Q-in-Q tunneling(Double VLAN)<br>GVRP(Generic VLAN Registration Protocol) | | |
| Link Aggregation | IEEE 802.3ad LACP/Static trunk<br>Supports 6 trunk groups with 4 ports per trunk | | |
| Spanning Tree Protocol | IEEE 802.1D Spanning Tree Protocol<br>IEEE 802.1w Rapid Spanning Tree Protocol<br>IEEE 802.1s Multiple Spanning Tree Protocol | | |
| Multicast | Dynamic/Static Multicast groups<br>IGMP Snooping v1,2,3<br>Port-based IGMP Snooping Fast Leave<br>GMP Querier | | |

# Product Specifications

## FR-7M3024 • FR-7M3024P • FR-7M3024BT



| Product | FR-7M3024 | FR-7M3024P | FR-7M3024BT |
|---|---|---|---|
| **Software Features** | | | |
| Rate Limitation | Per Port Rate Limitation<br>Ingress: 16-1000000 kbps/Egress: 16-1000000 kbps | | |
| Ring | ITU-T G.8032 ERPS, Recovery time<20ms | | |
| QoS | Traffic classification based, strict priority and WRR<br>8-level priority for switching<br>-Port number<br>-802.1p priority<br>-802.1Q VLAN tag<br>-DSCP/TOS field in IP Packet | | |
| ACL | IP-based ACL/MAC-based ACL<br>ACL based on:<br>-MAC Address<br>-IP Address<br>-Ethertype<br>-Protocol Type<br>-VLAN ID<br>-DSCP<br>-802.1p Priority | | |
| Security | Port Security<br>Static MAC address<br>IEEE 802.1x port-based network access control<br>RADIUS authentication<br>DHCP Snooping, DHCP option 82 | | |
| **PoE Management Functions (PoE Model)** | | | |
| PoE System Management | PoE Port status monitoring<br>Total PoE power budget control<br>PoE usage threshold and temperature threshold<br>PoE port Priority<br>PoE mode(PoE/PoE+/PoE++)<br>PD reboot(Zero Traffic Duration) | | |
| PoE Schedule | Absolute/Periodic Mode | | |
| **Layer 3 Functions** | | | |
| IP Interfaces | Max. 8 VLAN interfaces | | |
| Routing Table | Max.32 routing entries | | |
| Routing | IPv4 software static routing | | |
| **Management** | | | |
| Basic Management Interface | Console; Telnet; Web browser; SNMPv1/v2c | | |
| Secure Management Interface | SSHv2, TLSv1.2, SNMPv3 | | |

# Product Specifications

## FR-7M3024 • FR-7M3024P • FR-7M3024BT



| Product | FR-7M3024 | FR-7M3024P | FR-7M3024BT |
|---|---|---|---|
| **Management** | | | |
| System Management | Firmware Upgrade by HTTP protocol through Ethernet network<br>Configuration upload/download through HTTP<br>Remote syslog, System log<br>LLDP protocol, SNTP<br>PREVIEW NMS<br>Alarm(Relay, Led, Temperature, Trap, Power) | | |
| **Environmental** | | | |
| Operating Temperature | -40°Cto +75°C(-40 to 167 °F) | | |
| Storage Temperature | -40°Cto +85°C(-40 to 185 °F) | | |
| Operating Humidity | 5%~95% (non-condensing) | | |
| MTBF | 907,476 hours @ Telcordia SR-332 Standard | | |
| Cooling | Passive Cooling, Fanless Design | | |
| Noise Level | 0 dBA | | |
| **Regulatory & Warranty** | | | |
| ISO | Manufactured in ISO-9001facility | | |
| Safety | IEC62368-1:2020+A11:2020 | | |
| EMI | FCC Part 15B Class A, IEC 61000-3-2 | | |
| EMS | IEC61000-4-2 ESD: Contact:±8kV, Air:±15kV<br>IEC61000-4-5 Surge: Power: ±6kV; RJ45:±4kV/±6kV(PoE) | | |
| Shock | IEC 60068-2-27 | | |
| Free Fall | IEC 60068-2-32 | | |
| Vibration | IEC 60068-2-6 | | |
| Environmental | RoHS 2011/65/EU Annex II(EU) | | |

# Product Specifications



## Dimension (Unit: mm)




## Ordering Information

| Available Model | Description | Input Voltage | Operating Temp. |
|---|---|---|---|
| FR-7M3024 | L2+ Managed 24-port 24x10/100/1000BASE-T RJ45 Auto-MDI/MDI-X with Redundant DC Power Inputs | Dual 9-56VDC | -40 to +75°C |
| FR-7M3024P | L2+ Managed 24-port 24x10/100/1000BASE-T (PoE+) RJ45 Auto-MDI/MDI-X with Redundant DC Power Inputs | Dual 48-56VDC | -40 to +75°C |
| FR-7M3024BT | L2+ Managed 24-port 24x10/100/1000BASE-T (PoE++) RJ45 Auto-MDI/MDI-X with Redundant DC Power Inputs | Dual 52-56VDC | -40 to +75°C |

| Optional Accessories (to be purchased separately) | |
|---|---|
| Power Supply | Please select your power supply on our Power Supplies & Adapters page for details. |
| SFP Optical Transceiver | Please select your SFP on our SFP Modules page for details. |

| Package Contents | |
|---|---|
| Device | 1 x Industrial Ethernet Switch |
| Cable | 1 x DB9 female to RJ45 |
| Installation Kit | 1 x DIN-Rail Clip |

Specifications are subject to change without notice. Fiberroad Technology Co., Ltd. makes no warranties, either expressed or implied, regarding the information contained herein. Please contact us for the latest product information.

© Fiberroad Technology Co., Ltd. All rights reserved. | Oct 2026